

MARK TWAIN LAKE

WATER QUALITY

REPORT

for

1997

U.S. ARMY CORPS OF ENGINEERS, ST. LOUIS DISTRICT
ENVIRONMENTAL QUALITY SECTION - Water Quality

Ted Postol, Section Chief
Tori Foerste, Environmental Engineer
Donna Zoeller, Environmental Technician
Ron Frerker, Chemist

Table of Contents

<u>Water Quality Report-Mark Twain Lake</u>	<u>Page</u>
1.0 GENERAL OVERVIEW	1
2.0 WATER QUALITY ASSESSMENT CRITERIA	1
3.0 SPECIAL STUDIES	3
4.0 WATER QUALITY MONITORING RESULTS	3
5.0 SUMMARY OF MONITORING RESULTS	3
6.0 PLANNED 1998 STUDIES	4

LIST OF APPENDICES

Appendix A - Lake Map	A
Appendix B - Site Description	B
Appendix C - Laboratory Data/Graphs	C
Appendix D - Field Data/Graphs	D
Appendix E - Sediment Data	E
Appendix F - Division Report	F

LIST OF TABLES

<u>Table No.</u>	<u>Description</u>
2.1	State of Missouri - Water Quality Standards
C-1	Laboratory Data Summary
D-1	Field Data Summary - Site 22
D-2	Field Data Summary - Site 33
D-3	Field Data Summary - Site 66
D-4	Field Data Summary - Site 77
D-5	Percent Dissolved Oxygen Saturation
E-1	Laboratory Sediment Data Summary

LIST OF GRAPHS

<u>Graph No.</u>	<u>Description</u>
<u>Laboratory Data</u>	
C-1a	Alkalinity
C-1b	Chlorophyll & Pheophytin
C-1c	Bacteria (Fecal Coliform & Fecal Strep)
C-1d	Metals (Iron & Manganese)
C-1e	Silica, BOD & Chloride
C-1f	o- & Total Phosphate
C-1g	TSS, VSS & TDS
C-1h	TOC
C-1i	Nitrogen (Nitrate-N & Ammonia-N)
<u>Field Data</u>	
D-1a	Site 22 - May 1997
D-1b	Site 22 - July 1997
D-1c	Site 22 - September 1997
D-1d	Site 22 - October 1997
D-2a	Site 33 - May 1997
D-2b	Site 33 - July 1997
D-2c	Site 33 - September 1997
D-2d	Site 33 - October 1997
D-3a	Site 66 - May 1997
D-3b	Site 66 - July 1997
D-3c	Site 66 - September 1997
D-3d	Site 66 - October 1997
D-4a	Site 77 - May 1997
D-4b	Site 77 - July 1997
D-4c	Site 77 - September 1997
D-4d	Site 77 - October 1997
D-5	Dissolved Oxygen

WATER QUALITY MONITORING PROGRAM

Mark Twain Lake, Monroe City, Missouri

1.0 GENERAL OVERVIEW

Mark Twain Lake is located in northeast Missouri. The land surrounding the lake is used predominately for agriculture. The main agricultural contaminants into the watershed include pesticides and fertilizers. Also of concern is the high sediment loading into the lake and the colloidal characteristic of the sediments as well as low dissolved oxygen levels related to turbine generation. The lake is also susceptible to fish kills due to algal decay in the lake arms.

The operating purposes for Mark Twain Lake are fish/wildlife, hydroelectric power, flood control, recreation, navigation and water supply. The water quality management program for the lake includes monitoring of baseline parameters, ecological trends and investigation of problem areas to keep the lake within state and federal standards.

The water quality monitoring program was conducted during 1997 at three lake sites to assure that safe conditions were maintained for human recreation, wildlife and aquatic life. A special study of the North Fork Tributary was conducted in FY97 in an effort to determine contaminate levels as they enter the lake from a primary tributary. Five sampling events took place between May and November 1997. The location of the seven sampling locations (three lake and four North Fork Tributary) are depicted on the lake area map in Appendix A.

2.0 WATER QUALITY ASSESSMENT CRITERIA

The water quality assessment criteria are based on the State of Missouri regulatory limits for certain contaminants and generally accepted criteria for sustaining adequate aquatic plant and animal growth.

The following parameters were analyzed in FY97 sampling at Mark Twain Lake:alachlor, atrazine, chlorophyll, pheophytin-a, fecal coliform and fecal streptococcus bacteria, iron, manganese, nitrate-nitrogen, nitrate/nitrite-nitrogen, dissolved ammonia-nitrogen, alkalinity, total organic carbon (TOC), orthophosphate-phosphorus, total phosphate-phosphorus, total dissolved solids (TDS), total suspended solids (TSS), volatile suspended solids (VSS), biological oxygen demand (BOD), silica, chloride, pH, dissolved oxygen, specific conductance, temperature and oxidation-reduction potential.

The Missouri Department of Natural Resources, Code of State Regulations, Division 20, Chapter 7 classifies water quality criteria based on designated usage. These standards are used to determine the water quality of the lake. Table 2.1 provides a listing of the

regulatory limits for the parameters analyzed where a limit has been established.

TABLE 2.1

**State of Missouri
Water Quality Standards**

PARAMETER	LIMIT
Nitrate-Nitrogen	10 mg/l
Iron	0.30 mg/l
Manganese	0.05 mg/l
Fecal Coliform	< 200 colonies/100 ml
Chloride, Chronic	230 mg/l
Chloride, Acute	860 mg/l
pH	Range: 6.5 to 9.0
DO	> 5.0 mg/l
Atrazine	0.003 mg/l (Drinking Water Standard)
Alachlor	0.002 mg/l (Drinking Water Standard)

Monitoring of the alkalinity provides the measurement of the buffering capacity of lake water as well as the effect on the toxicity of certain pollutants in the water (i.e., algae blooms and decay). Ammonia nitrogen is monitored so that the effects on fish spawning, hatching, growth rate and pathologic changes in gills, liver and kidney tissue can be related to the detected levels of ammonia nitrogen. Nitrate-nitrogen degrades to nitrite or produces ammonia which has a detrimental effect on aquatic life and therefore is monitored to assure levels are below the regulatory "safe" limit. The metals manganese and iron are nutrients for both plant and animals. Phosphate is analyzed as phosphorus and is monitored due to the potential for uptake by nuisance algae. Levels of phosphate can indicate the potential for rapid growth of algae (algae bloom) which can cause serious oxygen depletion during the algae decay process. Serious oxygen depletion has a major effect on aquatic life. Photosynthetic activity can be hindered by the levels of total suspended solids. Total suspended solids concentrations which cause the photosynthetic activity to be reduced by more than 10% from the seasonably established norm, would have a detrimental effect on aquatic life. Silica, chlorophyll and pheophytin-a are monitored to provide indicators of algae growth and therefore potential oxygen depletion activity. Total volatile solids indicate the presence of organics in suspension and therefore additional demand levels of oxygen. Fecal coliform bacteria is monitored for the protection of human health as it relates to full body contact of lake waters. Chloride, pH and dissolved oxygen are monitored for the protection of aquatic life. Atrazine and Alachlor herbicides are commonly used agricultural chemicals which can be readily transported by rainfall runoff. Both compounds are suspected of causing cancer and therefore are monitored for the protection of human and aquatic health.

3.0 SPECIAL STUDIES

The collection of sediments at four lake sites and from three tributaries was continued in 1997. This study is being conducted to establish baseline levels. There is not a regulation for sediments. The composition of sediments vary for different areas. The

data may provide supplemental information as to the relative amount of contaminants transported by sediments versus contaminants dissolved in the water column. This study will provide useful information into what contaminants bottom fish and other aquatic life are ingesting. It would also give an indication into what reactions take place during lake turnover. Lake turnover can have an effect on the oxidizing of metals. Trend analysis of this data will be performed every five years. The parameters analyzed include: fourteen (14) priority pollutant metals, total phosphate (TPO₄), Kjeldahl nitrogen, nitrate-N (NO₃), total solids, total organic carbon (TOC), chlorinated pesticides and PCB's. The results for chlorinated pesticides and PCB analysis were below the detectable limits for 1997.

4.0 WATER QUALITY MONITORING RESULTS

The laboratory analytical results for water samples are summarized in Table C-1, Appendix C. Analytical results of detected levels are plotted in graphical form on Graphs C-1a through C-1h, Appendix C.

Field collected analytical results are summarized in Table D-1 through D-4, Appendix D. A graphical presentation of field results are presented in Graphs D-1a through D-4, Appendix D.

Laboratory results for sediment samples are summarized in Table E-1, Appendix E.

5.0 SUMMARY OF MONITORING RESULTS

The seasonal change brought on a gradual lake stratification during the summer months. The stratification was less dramatic than previous years and therefore overall sudden detrimental water quality changes such as algae blooms and dramatic dissolved oxygen reductions were not experienced in the lake system.

Bacteria levels were elevated in the early spring and could be attributed to surface water runoff carrying additional wildlife wastes into the lake during a time of seasonably increasing temperatures. Bacteria levels decreased to within acceptable limits throughout the remainder of the year.

The metals manganese and iron were seen at slightly elevated levels within the lake waters but no evidence exists that demonstrate the levels are detrimental to the overall lake system at this time.

Atrazine was detected at levels above the regulatory limit for drinking water standards. Treatment of water for the removal of atrazine is an expensive process and therefore elimination of the contaminant prior to water supply intake is the most cost effective approach. Management of agricultural application of the compound along with runoff management could reduce the influx into the lake system and therefore reduce the requirements for pretreatment of drinking water supplies originating from the lake.

The monitoring program for Mark Twain Lake during FY97 revealed a good water quality when compared to limits established by the MDNR for general use, secondary contact and indigenous aquatic life. Herbicide contamination and other agricultural nutrient runoffs are primary concerns for the lake water quality. Better land management practices, erosion control and buffering zones are methods to reduce these contaminants from entering the lake. The St. Louis District personnel will continue working with lake personnel, area communities and agencies in implementation of educational and implementation planning to bring about the use of better management techniques which will improve the lake water quality.

6.0 PLANNED 1998 STUDIES

Water quality monitoring at Mark Twain Lake was modified for FY97 from previous years monitoring programs. A special study of the North Fork Tributary was conducted in FY97 in an effort to determine contaminate levels as they enter the lake from a primary tributary. This work was conducted in cooperation with the Natural Resources Conservation Service (NRCS). An additional herbicide, Acedachlor, was added to the parameter list due to a request from NRCS. NRCS suspected that Acedachlor concentrations would be on the rise within the North Fork due to recent detection of the compound upstream. Acedachlor herbicide is apparently a commonly used herbicide in upland agricultural lands. FY98 monitoring is planned on the North, South and Middle Forks along with normal lake sampling. The parameter list will be expanded to include additional herbicides such as triazene and possibly others which are currently applied on upland agricultural properties. Cooperation and coordination of the project with the NRCS will continue during FY98.

A replacement real time thermistor string was installed in the vicinity of Behren's Access Area during FY97. The system replaces one destroyed by severe weather conditions. The new system allows for monitoring the lake temperature from five feet to forty feet on five foot intervals. The data obtained from the new system will assist the St. Louis District and lake personnel in monitoring fish spawning and potential water quality changes within the lake system. Currently the St. Louis District is preparing to post the data obtained from the system on the internet website to assist the lake personnel and general public in accessing the data during FY98.

The St. Louis District performed a hydroacoustic fish population survey at the discharge of the Clarence Cannon Dam during FY97. The survey was performed to determine the impact of a potential pump back operation at the facility. The St. Louis District is currently evaluating the feasibility of a pump back operation with the consideration for total water quality, wildlife impact and economics. The evaluation is ongoing for FY98.