

# ACTIVITY HAZARDS ANALYSIS

Date Prepared: February 9, 2010

Project: EC-HMQ

Prepared By: Karen M. González

Job: Chain Saw Operation

Reviewed By: Michael Henry

Risk Assessment Code(RAC):

L
---

E = Extremely High Risk  
 H = High Risk  
 M = Moderate Risk  
 L = Low Risk

		P r o b a b i l i t y				
		Frequent	Likely	Occasional	Seldom	Unlikely
S e v e r i t y	Catastrophic	<b>E</b>	<b>E</b>	<b>H</b>	<b>H</b>	<b>M</b>
	Critical	<b>E</b>	<b>H</b>	<b>H</b>	<b>M</b>	<b>L</b>
	Marginal	<b>H</b>	<b>M</b>	<b>M</b>	<b>L</b>	<b>L</b>
	Negligible	<b>M</b>	<b>L</b>	<b>L</b>	<b>L</b>	<b>L</b>

Recommended Protective Clothing & Equipment:

Proper Eye, Ear, Hand and Leg protection

Unlikely, Critical

JOB STEPS	HAZARDS	ACTIONS TO ELEMIMATE OR MINIMIZE HAZARDS	EM 385-1-1 (PARA REF)
Chain Saw Operation	Dismemberment, cuts, scrapes	<ol style="list-style-type: none"> <li>1. Check equipment for proper maintenance and operation.</li> <li>2. Eye, leg, and hearing protection shall be worn when you are operating this equipment.</li> <li>3. Chain saw should be set on the ground firmly for the starting operation.</li> <li>4. Two-hand contact should be maintained at all times during operation.</li> <li>5. All adjustments should be made with engine stopped.</li> <li>6. Do not cut stock higher than your belt.</li> </ol>	Section 13.F